

WiPG-1600

The enhanced WiPG-1600 supports **both wired and wireless connections** allowing greater networking flexibility and **new features** designed to inspire interactive meetings and learning.

Top Features



On Screen Annotation

Write and draw using the active annotation overlay.



Interactive Whiteboard

Click to switch from presentations to a white/blackboard.



1 to Many Distribution

Display to multiple network connected units simultaneously.



Power Over Ethernet

Power the wePresent units by Ethernet cable (PoE).



USB Media Player

Present directly from a USB token plugged into your unit.

SPECIFICATIONS

Operating Systems	Windows 7, 8, 10 and above Mac OS X 10.9 and above Android 4.0 and above iOS 9 and above
Video Outputs	1 x HDMI + 1 xVGA
Frame Rate	Up to 30 fps
Output Resolution	Up to 1080p
Number of Sources Simultaneously On Screen	Up to 4 (Fixed User Layout)
Number of Simultaneous Connections	Up to 64
Audio	Via HDMI, analog via Audio Jack 3.5mm
Authentication Protocol	WIFI WPA/WPA 2 PSK / WPA Enterprise
Wireless Transmission Protocol	2.4G(b/g/n)/ 5G(a/n) switchable
Reach	Up to 30m (100ft)
Connections	1 x 15 Pin VGA (back) 1 x RJ-45 Ethernet LAN (back) 1 x HDMI (back) 2 x USB 2.0 (front) + 1 x USB 2.0 (back) 1 x Stereo Phone Jack (back) 1 x LED Power Button (front) 1 x Reset Button (bottom)
Warranty	2 years (possible to extend)
Power	External power adaptor (5VDC, 2.6A), Power Over Ethernet (4.4W)
Power Consumption	15.3W (full load power consumption)
Heat Dissipation	18.755 BTU/hr
Mechanical	Weight: 801 g (with packaging) & 293 g (without) Dimensions: 216 x 220 x 66 mm (with packaging) 159 x 91 x 29.9mm (without)
Environment Temperature	Operation: 0° C~40° C & Storage: -10° C ~ +70° C
Environment Humidity	Operation: ≤ 90% & Storage: ≤ 85%RH

← SEE ALL FEATURES ON REVERSE

