



Port Settings

wePresent Network & Projection Protocols

	USAGE	DIRECTION	PORT #	NOTE
TCP	Command	Inbound	443	MirrorOp command.
			1689	MirrorOp command for debug log.
			3268	(back up if port 443 is not available.)
			389	
	Data	Inbound	8080	MirrorOp data.
			31865 515	(back up if port 8080 is not available.)
	Audio	Inbound	1688	MirrorOp audio.
	UoIP	Inbound	3240	wePresent UoIP feature.
			6000	wePresent UoIP feature.
	DLNA	Inbound	2869	DLNA CMD port for connection created
			49152 49153	DLNA streaming.
	AirPlay	Inbound	80 3689	Airplay streaming.
			7000	
7100				
7102				
49153				
UDP	Device Discovery	Inbound	1047	Used for device discovery to find available devices.
			1048	
			1049	
	DHCP	Outbound	67	DHCP daemon.
			68	
	SNMP	Inbound	161	SNMP protocol
			1900	SSDP broadcast used
	DLNA	Inbound	50000 - 65500	DLNA
	Airplay	Inbound	5353	Bonjour
			65353	Proxy service.
TCP/UDP	AirPlay	Inbound	554	

NOTE: Port TCP 5566, 5567 is for internal communication. (AirPlay)
Port TCP 19996 is for internal communication. (AirPlay)